

Multi Cleaner

Revision: 18/01/2023

Page 1 from 1

Technical data

Basis	Waterbased cleaning foam
Consistency	Liquid
Density	0,91 g/ml
Viscosity (Brookfield)	1 mPa.s
Flashpoint	> 100 °C
Acidity level (text)	> 8
Solubility in water	Fully soluble
Volatile Organic Compounds (VOC)	Ca. 14 %
Application temperature	15 °C → 25 °C

* These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. ** This information relates to fully cured product.

Product description

Multi Cleaner is a universal cleaning spray that sprays foam.

Properties

- Cleans and degreases
- Highly soluble
- Does not drip
- Leaves no residue

Applications

- Removes grease, wax, nicotine, soap residue and other dirt.
- A universal cleaning spray that sprays foam. This means it does not drip, making it ideally suited for cleaning vertical surfaces such as glass, tiles, mirrors, laminate, PVC, kitchens, car interiors, textile, carpets, office equipment, etc.
- Cleaning of air conditioner unit plate heat exchangers, cleaning of air pump indoor unit heat exchangers and all heat exchangers inside ventilation units.

Application method

Application method: Bring the aerosol to room temperature (to get optimal results). Shake can well before use. Apply Multi Cleaner on the surface to be cleaned. Let it work for about 20 seconds and then rub thoroughly until the surface is dry. Test for adverse effects on the surface in advance.

Health- and Safety Recommendations

In case of contact with eyes, wash immediately with plenty of water.

Dangerous. Respect the precautions for use.

Liability

The content of this technical data sheet is the result of tests, monitoring and experience. It is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.

Packaging

Colour: white foam

Packaging: 400 ml aerosol

Shelf life

3 years in unopened packaging in a dry and cool environment at temperatures between +5°C and +25°C.

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.