



# **Adhesive Remover Citrus**

Revision: 26/09/2023 Page 1 from 1

#### **Technical data**

Basis	Mixture based on low boiling solvents
Consistency	Liquid
Density	Ca. 0,85 g/ml
Viscosity (Brookfield)	1 mPa.s
Solubility in water	Not soluble
Volatile Organic Compounds (VOC)	97 %
Application temperature	5 °C → 30 °C

<sup>\*</sup> These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. \*\* This information relates to fully cured product.

# **Product description**

Adhesive Remover Citrus is a transparent solvent mixture suitable for removing fresh glue stains and for the cleaning and degreasing of metal surfaces.

### **Properties**

- Removes fresh glue stains
- Cleans and degreases
- Leaves no residue
- Fast drying
- Highly flammable
- Aerosol can be used in any angle (360°)

# **Applications**

- Transparent solvent mixture suitable for removing fresh glue stains and cleans brushes, palette knives and glue spatulas.
- · Removes hard excess contact glue.
- Powerful cleaner and degreaser of metals substrates. Also suitable for the preparation of surfaces for the application of sealants or adhesives.
- Not suitable for polystyrene and Plexiglas.

## **Packaging**

Colour: transparent Packaging: 400 ml aerosol

#### Shelf life

3 years in unopened packaging in a dry and cool environment at temperatures between +5°C and +25°C.

## Application method

Application method: Shake can well before use. Spray at a distance of appr. 20 cm of the object. Apply as required. After applying rub the surface dry with a clean towel. Always rub in one direction. Test for adverse effects on the surface in advance.

## **Health- and Safety Recommendations**

Use only in well-ventilated areas. In case of contact with eyes, wash immediately with plenty of water.

Dangerous. Respect the precautions for use.

## Remarks

 Due to the wide variety of possible plastics and paints and to avoid damage to the surface, a preliminary compatibility test is recommended.

## Liability

The content of this technical data sheet is the result of tests, monitoring and experience. It is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.

Remark: This technical data sheet replaces al previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.

 Soudal NV
 Everdongenlaan 18 - 20
 B-2300 Turnhout, Belgium

 Tel: +32 (0)14-42.42.31
 Fax: +32 (0)14-42.65.14
 www.soudal.com