

Clean All Genius Spray

Revision: 17/09/2021

Page 1 from 1

Technical data

Basis	Solvent mixture
Consistency	Liquid
Density	Ca. 0,76 g/ml
Solubility in water	Not soluble
Volatile Organic Compounds (VOC)	97 %
Application temperature	5 °C → 30 °C

* These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. ** This information relates to fully cured product.

Product description

Genius spray allows precise extrusion and regular spray action. Clean All Genius Spray is a multifunctional, fast-drying cleaner for machine parts, floors and other various surfaces.

Properties

- Leaves no residue
- Fast drying
- Aerosol can be used in any angle (360°)
- Contains non flammable propellant
- Cleans and degreases

Applications

- Suitable for cleaning and degreasing mechanical parts. Also suitable for the preparation of surfaces
- for the application of sealants or adhesives. For the removal of uncured excess MS, PU or silicone
- sealants, tar residue, grease, wax,... Can be used on most surfaces (metal, plastics, PVC,...) and leaves no residue.

Packaging

Colour: Transparent

Packaging: 300 ml aerosol

Shelf life

3 years in unopened packaging in a dry and cool environment at temperatures between +5°C and +25°C.

Substrates

All materials

Application method

Application method: Shake can well before use. Spray at a distance of appr. 20 cm of the object. Test for adverse effects on the surface in advance. Let it work for about 20 seconds and then rub thoroughly until the surface is dry. Apply as required.

Health- and Safety Recommendations

Use only in well-ventilated areas. In case of contact with eyes, wash immediately with plenty of water.

Remarks

- Due to the wide variety of possible plastics and paints and to avoid damage to the surface, a preliminary compatibility test is recommended.

Liability

The content of this technical data sheet is the result of tests, monitoring and experience. It is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.