

Contact Spray

Revision: 18/10/2022

Page 1 from 1

Technical data

Basis	Mixture based on mineral oil
Consistency	Liquid
Density	0,81 g/ml
Viscosity (Brookfield)	1 mPa.s
Flashpoint	52 °C
Acidity level (text)	Neutral
Solubility in water	Not soluble
Volatile Organic Compounds (VOC)	84 %
Temperature resistance**	-50 °C → 190 °C

* These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. ** This information relates to fully cured product.

Product description

Contact Spray is a universal spray for the cleaning and maintenance of electric contact areas.

Properties

- Rust and corrosion-resistant
- Improves transmission
- Prevents loss of tension
- Reduces humidity
- Non corrosive
- Water-repellent
- For in- and outdoor use
- Aerosol can be used in any angle (360°)

Applications

- Suitable for electric contact points such as switches, stop contacts, batteries, measuring tools, etc Cleans and deoxidizes surfaces and improves the power transmission at electric contacts. Prevents moisture penetration which could result in disturbances. Also suitable for dehumidising of electric
- wirework and – tools. Ideal for electric installations, appliances, stop contacts and light switches....

Packaging

Colour: transparent

Packaging: 400 ml aerosol

Shelf life

3 years in unopened packaging in a dry and cool environment at temperatures between +5°C and +25°C.

Substrates

All types of metals and plastics.

Application method

Application method: Shake can well before use. Switch off electrical equipment before spraying the product. Switch electric installations back on when spray is evaporated.

Health- and Safety Recommendations

Use only in well-ventilated areas. In case of contact with eyes, wash immediately with plenty of water. Dangerous. Respect the precautions for use.

Liability

The content of this technical data sheet is the result of tests, monitoring and experience. It is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.